# **HITACHI**

Reliable solutions





### **ZW-5 SERIES WHEEL LOADER**

Model: ZW80

Gross engine rated power: 63 hp/47.3 kW Operating weight: 12,210 lb (5,540 kg) Bucket ISO heaped: 1.2 yd³ (0.9 m3)

#### Heather Wilson

Internal Sales Support Rep (Central/West) HWilson@HitachiCM.us | 678-460-5968

#### Nathan Little

Sales Support Technical Specialist (Canada/East) NLittle@HitachiCM.us | 770-421-6854



**Engine:** Kubota V3307-DI-T **Horsepower:** 61 net

Gross engine rated power: 63 hp/

47.3 kW

Turn tipping load: 7,170 lb

## **HITACHI**

**Reliable solutions** 

#### **STANDARD EQUIPMENT**

- ROPS/FOPS canopy
- Safety articulation w/locking bar
- Tires: 17.5/65-20 10PR

#### **ALARMS (AUDIBLE)**

- Brake oil level
- Engine coolant temp
- Engine oil pressure

#### **ALARMS (VISUAL)**

- Air filter
- Battery discharge
- Brake oil level
- Engine coolant temp
- Engine oil pressure
- HST warning
- Machine service
- Machine stop

#### **GAUGES**

- Engine coolant temp
- Fuel level
- Hour meter
- Hydraulic oil level, sight

#### **OTHER**

- Hydrostatic transmission
- Neutral safety start
- Radiator dust screen
- Radiator, side-by-side w/oil cooler
- Reverse alarm
- Seat, adjustable suspension
- Shift lever lock
- Travel mode switch
- Bucket, coupler-type 1.18 cu. yd.
- Bucket leveler
- Coupler, hydraulic hook-type
- Counterweight
- Diff-lock (front axle only, grip switch activated)
- Fenders
- Linkage (Z-type, sealed w/HN bushings)

#### **OPTIONS**

#### **BUCKETS & ATTACHMENTS**

- 1.0 cu. yd. universal QC bucket (cannot be used with std hook-type QC)
- 48" X 48" pallet fork w/adjustable tines
- Hydraulic quick coupler, ISO or 418 Type
- Universal quick coupler, hyd (in lieu of std hyd hook-type QC)

#### STRUCTURAL ACCESSORIES

• Lifting eyes

#### **CAB ACCESSORIES**

 ROPS/FOPS cab w/HVAC (heat, vent, A/C)